

## Rain Gauge Tipping Bucket

### TR-525I Series Rainfall Sensor



### Description

The Texas Electronics, Inc. TR-525I Rainfall Sensor with 6" diameter funnel is a remote tipping bucket style rain gauge that measures liquid precipitation. The Rain Gauge is a freestanding receptacle for measuring precipitation. Through an opening at the top of the device, rain is collected and then funneled to a mechanical device, called a tipping bucket. As water is collected, the tipping bucket fills to the point that it tips over, causing a momentary closure of a switch to incrementally measure rainfall accumulation. This action empties the bucket in preparation for additional measurement. Water discharged by the tipping bucket passes out of the rain gauge with no need for emptying. The TR-525I is a rugged and reliable rain gauge that delivers high accuracy at a low cost.

### Features & Benefits

- Interfaces with virtually all data acquisition systems
- Knife-edge collector optimizes rainfall catch
- Exceptional splash-out protection improves accuracy in high winds
- Easy installation and maintenance
- Over 30 years in production
- Lightweight aluminum exterior
- Powder coated aluminum collector for weather resistance and better water shedding
- Integrated bubble level
- 2 thumb screws to hold collector secure

### Specifications

Resolution:	0.01" English, 0.2 mm (optional)
Accuracy:	0-2 in. (50 mm) per hour; +/-1%
Range:	27" (700 mm) per hour
Collector diameter:	6.06" (163 mm)
Funnel depth:	>6.5" (165 mm)
Splash out protection:	>2" (50 mm)
Operating Temp:	32 to 158° F (0 to 50° C)
Storage Temp:	-40 to 185° F (-40 to 70° C)
Humidity Limits:	0 to 100%
Weight:	4 lbs.
Height:	10.25"
Cable:	10', 24 gauge 2 conductor
Switch:	Momentary potted reed switch
Switch rating:	30 VDC @ 2 A, 115 VAC @ 1 A
Switch Closure Time:	135 ms
Bounce Settling Time:	0.75 ms
Pivot:	Ground bronze pivots with hardened stainless steel shaft
Bucket:	Black ABS injection molded
Level:	Integral Bubble Level
Warranty:	3 years

### Description

Installation consists of attaching the three sensor support legs to a firm platform (such as our MB-525 Mounting Base). Pole mounting on the mast of a weather station is available by securing to the included side bracket.

Maintenance consists of routine cleaning of debris from the filter screen, and occasional calibration verification with our FC500 Field Calibration Kit.

### Ordering Information

Model #: TR-525I  
 Description: Rain Gauge, 6.06" collector, English  
 (Please specify for calibration of 0.2 mm/tip)

### Optional Parts / Accessories

HOBO Pendant Datalogger  
 MB-525 Pole Mounting Base  
 FC-500 Field Calibration Kit  
 BB-525 Bird Repellent  
 HT-525 Heater, 120 VAC